

Available with or without an IMT telescopic crane or loadgate, our Dominator® Contractor Series (CS) 11-foot non-crane body is available with standard 52-inch right- and left-hand side packs or an optional 60-inch right front raised side pack.

> BASE BODY SPECIFICATIONS

Body Size	Body Configuration ¹	Body Rating	Body Weight ^{2,3}	Body Width	GVWR	Storage Capacity ³	Angle of Departure	Chassis CA ⁴	Max. IMT Crane Model
11' (3.4 m)	LH&RHSTD	20,000 ft-lb (2.8 tm)	3300 lb (1497 kg)	96" (2.4 m)	16,000-19,500	125.87 cu ft (3.6 m³)	13°	84" (2.1m)	2020
11' (3.4 m)	RFRSD	20,000 ft-lb (2.8 tm)	3355 lb (1522 kg)	96" (2.4 m)	16,000-19,500	131.25 cu ft (3.7 m³)	13°	84" (2.1m)	2020

¹ Standard (STD) = 52", Raised (RSD) = 60". 2 Includes doors, side packs, workbench. 3 Body weight and storage capacity are estimated based on product configuration.

⁴ Does not include welder deck.



> STANDARD FEATURES

- IMT CMD.CTRL™
- IMT Patented Inverted A-Frame Design
- · Complete System Integration Including Body, Crane, and Compressor
- Three-Point Access Package (workbench configuration - no loadgate)
- · Automotive-Style Electrical Harnessing
- IMT Compartment Coating (VOC-compliant polyurethane modified multicolor spray finish)

> OPTIONS

- · High-Intensity LED Lighting Package
- · Axalta Bedliner
- · Drawer Sets, Adjustable Shelves
- 3" (7.6 cm) Divided Adjustable Shelves
- · Lightweight, Adjustable Bolt Bins
- Stabilizers Manual
- · Workbench Vises and Vise Plates
- · Loadgate or Workbench Bumper with Through Compartment
- · Compartment Pressurization System
- · Compressed Air and Welding Systems
- · Headache Rack
- · Master Lock System

> COMPATIBLE IMT CRANES

ELECTRIC

- 1015E
- $\bullet \quad 2020 E \ \ (Workbench \ configuration no \ loadgate) \\$
- 3203i
- $\bullet \quad 4004i \ \ (\text{Workbench configuration-no loadgate}) \\$

HYDRAULIC

- 1015
- 2020 (Workbench configuration no loadgate)



COMPLETE REMOTE CONTROL

Control your chassis, crane functions, service body components and air compressor remotely. IMT CMD.CTRL™ combines strong, reliable hardware with flexible, intuitive software to give operators a productive, user-friendly experience.



HIGH-INTENSITY LED LIGHTING

LED light bars provide superior light penetration for enhanced visibility.



BODY SUBSTRUCTURE

Patented A-Frame design with integrated crane box is engineered for maximum strength and weight reduction.



An Oshkosh Corporation company

Iowa Mold Tooling Co., Inc. | 500 Highway 18 West | Garner, Iowa 50438 | 800-247-5958 | imt.com









